

## Product description

Self adhesive foam strip for use in combination with UNI-Rivets to fix EQUITONE façade panels to a metal support frame.

The foam strip is designed to create a watertight seal with a minimal amount of force. It also minimizes vibrations of the façade panel and prevents contact between uncoated fibre cement and aluminium sub frame. Once in place, the foam will be able to handle normal joint movement due to thermal and hygric expansion and shrinkage or environmental forces.

ARTICLE NUMBER: 4085481

## 1. Technical Characteristics

Tape material	PU elastomer
Dimensions (w x h)	9 x 5 mm
Density	30 kg/m <sup>3</sup>
Weight	± 1.35 g/m
Colour	dark grey
Flame rating	HF-1 self-extinguishing acc. UL94
Tensile strength (ISO 1798)	≥ 95kPa
Elongation (ISO 1798)	≥ 115 %
Adhesive	solvent free
Liner	PE film, white, thickness 60 µm
Service temperature	- 40 to + 90 °C
Application temperature	+ 5 to + 50 °C
Apply to clean, dry surfaces only	



## 2. Storage

Material should be stored dry, dust free and at temperature above 10°C to guarantee optimal gluing performance in application.

Shelf life : max. 18 months

## 3. Packaging

100 m per roll

## 4. Processing

Consult the application guidelines for façade panels rivet fixed on a metal sub-construction.

---

### Disclaimer

The information in this document is correct at time issuing. However, due to our committed program of continuous material and system development we reserve the right to amend or alter the information contained therein without prior notice. Please visit [www.equitone.com](http://www.equitone.com) to ensure you have the most current version. All figures contained in this document are illustrations and should not be used as construction drawings. This information is supplied in good faith and no liability can be accepted for any loss or damage resulting from its use. This document is protected by international copyright laws. Reproduction and distribution in whole or in part without prior written permission is strictly prohibited. EQUITONE and logos are trademarks of Etex NV or an affiliate thereof. Any use without authorisation is strictly prohibited and may violate trademark laws.