

#### EQUITONE Perforated Closure Material Information Sheet

# Product description

Perforated closures to prevent entry of birds and vermin in the cavity. Used for façades with EQUITONE.

Perforation

surface

139 cm<sup>2</sup>/m

92 cm<sup>2</sup>/m

185 cm<sup>2</sup>/m

92 cm<sup>2</sup>/m

254 cm<sup>2</sup>/m

393 cm<sup>2</sup>/m

Perforation

34 %

30 %

37 %

30 %

36 %

39 %

ARTICLE NUMBER:	40/30	: natural 4054138 - black 4071097
	50/30	: natural 4006485 - black 4071098
	70/30	: natural 4006486 - black 4071099
	100/30	: natural 4006488 - black 4071100

#### 1. Technical characteristics

Perforation

both legs

both legs

long leg

long leg

Dimensions	40/30 mm, 50/30 mm, 70/30 mm, 100/30 mm
Length	2.50 m
Thickness	0.8 mm
Colour	natural aluminium or black aluminium

long leg

short leg

long leg

short leg





# 2. Packaging

Type-

40/30 mm

50/30 mm

70/30 mm

100/30 mm

Packaging

Per piece

### 3. Processing

Read the application guidelines for EQUITONE before installation.

#### Disclaimer

The information in this document is correct at time issuing. However, due to our committed program of continuous material and system development we reserve the right to amend or alter the information contained therein without prior notice. Please visit www.equitone.com to ensure you have the most current version. All figures contained in this document are illustrations and should not be used as construction drawings. This information is supplied in good faith and no liability can be accepted for any loss or damage resulting from its use. This document is protected by international copyright laws. Reproduction and distribution in whole or in part without prior written permission is strictly prohibited. EQUITONE and logos are trademarks of Etex NV or an affiliate thereof. Any use without authorisation is strictly prohibited and may violate trademark laws.



