

# EQUITONE Foam Tape (Option 1) Material Information Sheet

## Product description

Self adhesive foam strip for use in combination with UNI-Rivets to fix EQUITONE façade panels to a metal support frame.

The foam strip is designed to create a watertight seal with a minimal amount of force. It also minimizes vibrations of the façade panel and prevents contact between uncoated fibre cement and aluminium sub frame. Once in place, the foam will be able to handle normal joint movement due to thermal and hygric expansion and shrinkage or environmental forces.

ARTICLE NUMBER: 4006465

#### 1. Technical Characteristics

Material	closed cell PVC foam self adhesive
Liner	Paper
Dimensions (w x h)	9 x 6 mm
Weight	± 7 g/m
Colour	black
Hardness (ASTM D2240)	14 Shore 00
Tensile strength (DIN 53571)	16 N/cm²
Elongation (DIN 53571)	200 %
Adequate seal at minimum	30% compression
Service temperature	- 30 to + 70 °C
Application temperature	+ 5 to + 50°C
Apply to clean, dry surfaces only	





#### 2. Storage

Material should be stored at  $21\,^{\circ}$ C, 50% relative humidity to guarantee optimal gluing performance in application.

#### 3. Packaging

15 m per roll

### 4. Processing

Consult the application guidelines for façade panels riveted on an aluminium sub-construction.

#### Disclaimer

The information in this document is correct at time issuing. However, due to our committed program of continuous material and system development we reserve the right to amend or alter the information contained therein without prior notice. Please visit www.equitone.com to ensure you have the most current version. All figures contained in this document are illustrations and should not be used as construction drawings. This information is supplied in good faith and no liability can be accepted for any loss or damage resulting from its use. This document is protected by international copyright laws. Reproduction and distribution in whole or in part without prior written permission is strictly prohibited. EQUITONE and logos are trademarks of Etex NV or an affiliate thereof. Any use without authorisation is strictly prohibited and may violate trademark laws.